

Glass Conductivity Cell K=0.1 (Mini DIN)



The E8075 Glass Conductivity Cell is for dip applications where the sample conductivity is low and the standard E8071 general purpose conductivity cell does not have the required sensitivity.

Typical applications could range from checking the quality of de-ionized or distilled water to sensitive analysis of ecological water sources.

The 12mm glass body has two internal active platinum electrodes in close proximity which have to be submerged in the samples to a minimum depth of around 2cm.

The E8075 Conductivity cell is suitable for use with the Series 4 QP481 and QP458 conductivity meters only and contains a temperature sensor to enable all readings to be temperature compensated (ATC). Calibration solutions are available and the recommendation for general purpose cells is to calibrate using a 1413uS/cm standard such as EDT A3052 and A3053.

Temperature reading and compensation range is 0-50 degrees centigrade. For general analysis above 500uS/cm use a K=1 cell (E8071). For process measurements or where the use of glass is not acceptable EDT manufacture a complete range of Conductivity cells to suit most applications.

The E8075 Conductivity cell has a fixed 1 metre cable with a Mini DIN connector to fit EDT Series 4 meters. We also manufacture conductivity cells compatible with most models and make of instrument. Contact us so we can advise the part number and price.

Specifications

Body Type	Glass
Cable Length	1M
Cap Diameter	16mm
Conductivity Cell Range	0.1 μ S-2000 μ S
Cell Type	Platinum Plates
Connector	Mini DIN
Diameter	12mm
Length	155mm

Related Products



1413 μ S/cm
Conductivity Standard



K=1 Glass Conductivity
Cell (Mini DIN)



1413 μ S/cm Standard
(500ml)

www.edt.co.uk/e8075

